

OIL FIRED FURNACES

Light commercial

AMT 300 / AMT 400
AMP 300



AMT 300

AMT 400



AMP 300

FEATURES

- Lowboy or Highboy (AMP multi-position)
- Stainless steel combustion chamber
- Low speed manual blower switch
- 4 speed PSC motor (Belt drive on AMT 400)
- Beckett or Riello burner
- Air filter (AMT only)
- Designed to adapt an air-conditioner or a heat pump
- 3-Position installation (AMP)



www.dettson.com

OIL FIRED FURNACES

Light commercial AMT 300 / AMT 400 and AMP 300

TECHNICAL DATA SHEET

MODELS	AMT 300	AMT 400	AMP 300
INPUT (BTU/h)	168,000 @ 210,000	245,000 @ 350,000	168,000 @ 210,000
OUTPUT (BTU/h)	141,000 @ 173,000	209,000 @ 286,000	142,000 @ 175,000
EFFICIENCY	Up to 86.7%	Up to 85.5%	Up to 86.3%
WARRANTY ON PARTS	1 year	1 year	1 year
WARRANTY ON HEAT EXCHANGER	10 years	10 years	10 years
BURNER	Beckett or Riello	Beckett or Riello	Beckett or Riello
EVACUATION	Chimney	Chimney	Chimney
PROFILE / FLUE	Low Boy / Rear	Low Boy / Rear	High Boy / Front
WIDTH (in)	21¼	26	24¼
DEPTH (in)	54¾	66⅞	34
HEIGHT (in)	36¼	46⅞	53
SUPPLY (in)	20 x 24	23¾ x 29¾	22 x 30
RETURN (in)	20 x 22	23¾ x 25¾	28 x 18
FLUE PIPE (in)	7	8	7



3400, boulevard Industriel, Sherbrooke, Quebec, J1L 1V8, Canada
 Phone: 1.819.346.8493 | Fax: 1.819.822.4227
 info@dettson.ca | www.dettson.com

